

# SCARIFIERS

PRODUCT CATEGORY



GRINDERS & POLISHERS



SHOTBLASTERS



FLOOR REMOVAL



SCARIFIERS



SCREED



TROWELS



BARTELL

morrison

SPE

Innovatech

CONTEC NORTH AMERICA


PRECISION METAL WORKS



SAWS



TOOLING & CONSUMABLES



DIAMOND BLADES



SPREADERS



COMPACTION



GENERATORS



MIXERS



BARTELLGLOBAL.COM

# FEATURES AND BENEFITS

## BEF 200N



### FEATURES

- Rigid, compact design
- Quick Lift - Pulls Cutters In/Out of Cut
- 50mm (2") dust extraction port
- Dust free when operated with a suitable vacuum
- Large diameter wheels for excellent mobility and stability
- Welded construction is rigid and strong
- Fine Adjust- Screw type raise and lower control
- Firm engine mounting plate
- Front wheels protected from debris
- Height adjustment at the handle

## BEF 275



### FEATURES

- 50mm (2") dust extraction port
- Dust free when operated with recommended vacuum
- Six flail shafts, heavy duty TCT cutters
- Large wheels for excellent mobility & stability
- Forward mounted cutter drum for perfect balance
- Side plate access for easy drum removal
- Adjustable handle
- Strong and rigid design
- Accurate depth control

## BEF 320



### FEATURES

- 50mm (2") dust extraction port
- Dust free when operated with recommended vacuum
- Hydraulic drum raise and lower
- Variable speed
- Self-propelled, hydrostatic drive
- Forward and reverse controls
- Up-cutting drum for efficiency
- Heavy-duty build
- Accurate depth control

# COMPLETE LINE

## BEF 200N

### TECHNICAL SPECS

Type	Electric (1 Phase)	Electric (1 Phase)	Electric (3 Phase)	Gas / Petrol
<b>Part Number</b>	BEF 200N-1	BEF 200N-2 (A)	BEF 200N-3	BEF 200N-4( A)
<b>Power Output</b>	3hp / 2.2kW	3hp / 2.2kW	3hp / 2.2kW	<b>(Gross)</b> 5.5hp/4kW
<b>Voltage</b>	110V	230V	-	-
<b>Cutter Head Speed</b>	1738 RPM	1738 (2090)	1738 RPM	1833 RPM
<b>Length</b>	990mm (39")	990mm (39")	990mm (39")	990mm (39")
<b>Width (Body)</b>	375mm (15")	375mm(15")	375mm (15")	360mm (14")
<b>Width (INCL. Handle)</b>	429mm (16")	429mm (16")	429mm (16")	429mm (16")
<b>Height</b>	942mm (37")	942mm (37")	942mm (37")	942mm (37")
<b>Weight</b>	62kg (137lbs)	62kg (137lbs)	62kg (137lbs)	58kg (127lbs)
<b>Working Width</b>	200mm (7.9")	200mm (7.9")	200mm (7.9")	200mm (7.9")
<b>Working Distance from Wall</b>	60mm (2.4")	60mm (2.4")	60mm (2.4")	50mm (1.9")
<b>Engine RPM</b>	-	-	-	3000 RPM
<b>Motor RPM</b>	2870 RPM	2870 (3450)	2870 RPM	-

## BEF 275

## BEF 320

### TECHNICAL SPECS

Type	Petrol / Gas	Electric	Electric	Electric	Diesel
<b>Part Number</b>	BEF 275-1	BEF 275-2	BEF 275-7	BEF 320-1A	BEF 320-3A
<b>Power Output</b>	11hp / 8.2kW	10hp / 7.5kW	10hp / 7.5kW	15hp / 11.2kW	10hp / 7.5kW
<b>Voltage</b>	-	400v / 460v	230v 3 Phase	400/460v 3 Phase	-
<b>Cycles</b>	-	50 / 60Hz	50 / 60Hz	50 / 60 Hz	-
<b>Cutter Head Speed</b>	1640 RPM	1640 RPM	1640 RPM	933 RPM	1333 RPM
<b>Starter</b>	-	-	-	Star / Delta	Manual
<b>Travel Speed</b>	-	-	-	0-12 m/min (0-39 ft/min)	0-12 m/min (0-39 ft/min)
<b>Length</b>	1220mm (48")	1220mm (48")	1220mm (48")	1230mm (48.4")	1230mm (48.4")
<b>Width</b>	511mm (20.1")	511mm (20.1")	511mm (20.1")	590mm(23.2")	590mm(23.2")
<b>Height</b>	900mm (35.4")	900mm (35.4")	900mm (35.4")	1220mm (48")	1220mm (48")
<b>Weight</b>	145kg (319lbs)	150kg (331lbs)	150kg (331lbs)	339kg (749lbs)	319kg (702lbs)
<b>Working Width</b>	275mm (10.8")	275mm (10.8")	275mm (10.8")	320mm(12.6")	320mm(12.6")
<b>Working Distance from Wall</b>	65mm (2.6")	65mm (2.6")	65mm (2.6")	40mm(1.6")	40mm(1.6")
<b>Engine RPM</b>	3000 RPM	2800 RPM	2800 RPM	-	-