











TECHNICAL SDECS

BEF275

BEF320

| TECHNICAL SPECS | | |
|----------------------------|--------------------------|-----------------|
| Part Number | BEF 320-1A | BEF 320-3A |
| Engine/Motor Type | Electric | Diesel |
| Power Output | 15hp / 11.2kW | 10hp / 7.5kW |
| Voltage | 460V 3-Phase | _ |
| Cycles | 50/60Hz | _ |
| Cutter Head Speed | 933 | 1333 |
| Starter | Star / Delta | Manual |
| Travel Speed | 0-39 ft/min (0-12 m/min) | |
| Length | 48.5" (123cm) | |
| Width | 23.25" (59cm) | |
| Height | 48" (122cm) | |
| Weight | 749 lbs (339kg) | 702 lbs (319kg) |
| Working Width | 12.5" (32cm) | |
| Working Distance from Wall | 1.5" (4cm) | |

BEF320

HEAVY-DUTY PLANING AND PREPARATION

Bartell Global's line of SPE scarifiers has been proven by contractors around the world for over 30 years. Many years experience in design and operation of surface preparation equipment have been integrated with cuttingedge computer aided design, resulting in the BEF320 Concrete Scarifier: the most advanced machine of its type.

FEATURES

- · 13 inch (320mm) working width
- · 2 inch (5cm) dust extraction port
- · Dust free when operated with recommended dust collector
- · Hydraulic drum raise and lower
- · Accurate depth control for precise surface textures and maximum cutter life
- · Variable speed
- · Self-propelled, hydrostatic drive
- · Forward and reverse controls
- · Up-cutting drum for efficiency

APPLICATIONS

- · Cleaning and texturing concrete and asphalt
- · Removal of paint, rust, grease, ice deposits, line markings, and concrete laitance
- · Removal of waterproof membranes
- · Thermoplastic line removal
- · Grooving applications

