



HOT COMPRESSED AIR HCA 300 & 520



The SPE HCA300 & HCA520 hot compressed air surface treatment systems employ a unique diesel driven, self contained design enabling them to be operated without the need for a separate air compressor. They are high performance, heavy duty machines for the treatment of oil impregnated concrete floors, general drying for road markings, and wet/damp surfaces prior to various applications. It can also be used to clean and heat road joints, and for softening prior to re-texturing.

| Specifications | | |
|--------------------|------------------------------|------------------------------|
| Type | HCA Pedestrian System Diesel | HCA Pedestrian System Diesel |
| Part Number | HCA-520 | HCA-300 |
| Machine Dimensions | | |
| Length | 1480mm (58.3") | 1480mm (58.3") |
| Width | 680mm (26.8") | 680mm (26.8") |
| Height | 980mm (38.6") | 980mm (38.6") |
| Weight | 122kg (268lbs) | 122kg (268lbs) |
| Working Width | 520mm (20.5") | 300mm (11.8") |
| Engine Output | 7hp/5.2kW | 7hp/5.2kW |



Applications

- Treatment of oil impregnated floors
- General drying of wet/damp surfaces prior to various applications
- General drying of road markings
- Clean and heat road/bridge joints
- Surface softening prior to re-texturing

Features

- Unique process
- No compressor required
- Portable
- Easily operated
- Fail safe system



1-866-501-1683
375 Annagem Blv. Mississauga,
ON, Canada, L5T 3A7
www.bartellmorrison.com

1-888-999-1570
200 Commerce Dr. Freehold,
NJ, U.S.A, 00728
www.bartellmorrison.com

44-(0)1673-860709
Honeyholes Lane, Dunholme
Lincoln. LN2 3SU. U.K.
www.spe-int.com

1-800-267-6682
832 80th St. SW. Everett,
Washington, U.S.A, 98203
www.innovatechproducts.com