

# 16ES & 16DC

## SHOTBLASTER & DUST COLLECTOR



**SPE 16ES**  
SHOT BLASTER



**SPE 16DC**  
DUST COLLECTOR

TECHNICAL SPECS	SPE 16ES	16DC	DESIGN FEATURES
<b>Voltage</b>	380-415V	230V / 460V	<ul style="list-style-type: none"> <li>• Blast unit constructed of manganese steel</li> <li>• Dust collector fitted with integral compressor and reverse air jet pulsation system to allow continuous working</li> <li>• Blasting width can be reduced for line removal and weld inspection</li> <li>• Self propelled variable speed drive allows complete operator control</li> <li>• Grill fitted into hopper assembly to keep foreign objects from entering the blastwheel and causing damage</li> <li>• Capable of using up to S550 abrasive</li> <li>• Fully machined blastwheel support bearing assembly (eliminates bearing problems, automatically self-aligns blastwheel components)</li> <li>• Blastwheel can be rotated in both directions (Optional extra)</li> <li>• Can be dismantled to pass through a 24" (600mm) access hole in storage tanks</li> </ul>
<b>Phase</b>	3-Phase		
<b>Blast Motor Output</b>	15hp (11kW) 20hp (15kW)	-	
<b>Cycles</b>	60Hz		
<b>Cleaning Width</b>	16" (406mm)	-	
<b>Length</b>	49" (1250mm)	68" (1730mm)	
<b>Width</b>	20" (510mm)	40.5" (1030mm)	
<b>Height</b>	49" (1250mm)	63" (1600mm)	
<b>Weight</b>	882lbs (400kg)	882lbs (400kg)	
<b>CFMS</b>	-	1300/1560 ft <sup>3</sup> /min	



SPE 9G



SPE 9ES



SPE 12ES



SPE 16ES



SPE 20ES



SPE 20ES  
ELECTRIC DRIVE