

20ES & 20DC

SHOTBLASTER & DUST COLLECTOR



SPE 20ES
SHOT BLASTER



SPE 20DC
DUST COLLECTOR

TECHNICAL SPECS	SPE 20ES	20DC	DESIGN FEATURES
Voltage	380-415V	230V / 460V	<ul style="list-style-type: none"> • Manganese steel construction • Blasting width can be adjusted for line removal and weld inspection • Self-propelled and variable speed drive • Grill fitted into hopper assembly to keep foreign objects from entering the blastwheel and causing damage • Capable of using up to S550 abrasive • Fully machined blastwheel support bearing assembly (eliminates bearing problems and automatically self-aligns blastwheel components) • Can be dismantled to pass through a 24" (600mm) access hole in storage tanks • Removes rubber deposits • Removal of old coatings • Steel preparation to SA3 standard • Provides non-slip surfaces
Phase	3-Phase		
Blast Motor Output	30hp (22.5kW)	-	
Cycles	60Hz		
Cleaning Width	20.5" (520mm)	-	
Length	59.5" (1511mm)	68.1" (1730mm)	
Width	23.5" (597mm)	31.5" (800mm)	
Height	57" (1448mm)	63" (1600mm)	
Weight	1459lbs (662kg)	770lbs (350kg)	
CFMS	-	1300/1560 ft ³ /min	



SPE 9G



SPE 9ES



SPE 12ES



SPE 16ES



SPE 20ES



SPE 20ES
ELECTRIC DRIVE